



## Thermo Scientific Orion Star A326

pH/RDO/Dissolved Oxygen Portable Meter

The Thermo Scientific Orion Star A326 pH/RDO/Dissolved Oxygen Portable Meter is the top choice for advanced pH and dissolved oxygen measurements on location. Get the information you need quickly and easily from the large, backlit graphic LCD display. Informative display shows individual pH/mV/RmV or dissolved oxygen in percent saturation or concentration results with temperature, or all results at once. Additional helpful information include electrode status, time, date, sample ID, user ID and calibration points. Advanced features such as stability and averaging options provide additional options allowing for laboratory accuracy everywhere you need it.



### Features and Benefits

- Anyone can use this meter with its plain language screen prompts, soft keys that update for easy selection and a multilanguage interface that supports English, Spanish, French, Italian, German and Chinese
- Don't miss a reading – AUTO-READ™ locks in the stable reading on your screen, ready indicator alerts when readings are stable and timed reading gathers data in specific time intervals
- Up to 5 point pH calibration with automatic recognition for USA/NIST and DIN buffers
- Fix pH calibration errors without a complete recalibration with calibration editing
- No need to worry about DO probe compatibility – the meter accepts and automatically recognizes Orion polarographic and RDO optical/luminescence-based probes
- Easily get accurate DO results with automatic temperature, manual salinity and automatic/manual barometric pressure correction
- Calibrate DO using water-saturated air, air-saturated water, a Winkler titration or zero point calibration
- Non-volatile memory holds up to 5000 data points with time and date stamp
- User and sample ID fields for additional data accuracy
- Stores up to 10 methods allow for customized procedures to differentiate between tests and/or users
- Easily transfer data and keep meter software up-to-date with the USB and RS232 ports and complimentary data analysis software
- Four AA batteries (included) provide over 800 hours of operation or purchase the universal power adapter (sold separately) to use on AC power
- Perfectly portable, waterproof and protected to take anywhere with a IP67-rated housing
- 3 year meter replacement warranty



### Product Specifications

CE   TUV   FCC		
pH	Range	-2.000 to 20.000
	Resolution	0.1, 0.01, 0.001
	Relative Accuracy	±0.002
	Calibration Points	Up to 5
	Calibration Editing	Yes
mV/Rel mV/ ORP	Range	±2000.0 mV
	Resolution	0.1
	Relative Accuracy	±0.2 mV or ±0.05 % of reading whichever is greater
	E <sub>n</sub> ORP Mode	Yes
Dissolved Oxygen	<b>Concentration - Polarographic</b>	
	Range	0 to 90 mg/L
	Resolution	0.01, 0.1
	Relative Accuracy	±0.2
	<b>% Saturation - Polarographic</b>	
	Range	0 to 600
	Resolution	0.1, 1
	Relative Accuracy	±2 %
	<b>Concentration - RDO</b>	
	Range	0 to 50 mg/L
	Resolution	0.01, 0.1
	Relative Accuracy	±0.1 mg/L up to 8 mg/L; ±0.2 mg/L from 8 to 20 mg/L; 10 % of reading from 20 to 50 mg/L
	<b>% Saturation - RDO</b>	
	Range	0 to 500
	Resolution	0.1, 1
	Relative Accuracy	±2 %
	Manual Barometric Pressure Correction	450.0 to 850.0 mm Hg
	Manual Salinity Factor Correction	0 to 45 ppt
	Calibration Features	Water-saturated air, air saturated water, manual (Winkler) and zero point
	Probe Characteristics	Polarographic or RDO
Temperature	Range	0 to 50 °C, 32 to 122 °F
	Resolution	0.1
	Relative Accuracy	±0.1
	Offset Calibration	1 point
Datalogging	Number of Datalogs	5000 with time and date stamp
	Log Function	Manual, ready (includes AUTO-READ™), timed
Inputs	pH Electrode	BNC, reference pin
	DO with Temp. Probe	9-pin mini-DIN
Output		RS232, USB
Power	AC Adapter	Optional – universal, 100-240 VAC
	Battery Power	Optional – 4 AAs
	Battery Life	800 hrs

### Meter Ordering Information

Cat. No.	Description
STARA3260	<b>Orion Star A326 pH/RDO/Dissolved Oxygen Portable Multiparameter Meter</b> - Four AA batteries (installed)
STARA3265	<b>Orion Star A326 pH/RDO/Dissolved Oxygen Portable Multiparameter Meter Kit</b> - 8107UWMMMD Orion ROSS Triode 3-in-1 pH/ATC probe, 3m cable - 087010MD Orion RDO optical/luminescence-based probe with 3m cable, stainless steel guard, calibration sleeve and optical/luminescence-based cap - 910410 Orion pH 4.01 buffer, 10 pouches - 910710 Orion pH 7.00 buffer, 10 pouches - 911010 Orion pH 10.01 buffer, 10 pouches - 810001 Orion ROSS electrode storage solution, 475 mL - 01100710 Orion 1413 µS conductivity standard, 10 pouches - 911110 rinse solution, 10 pouches - Protective armor with electrode holder - Hard carrying case - Four AA batteries (installed)

### Accessories

Cat. No.	Description
STARA-CS	Hard carrying case for Orion Star A-series portable meters
STARA-AR	Armor for Orion Star A-series portable meters, includes electrode holders for pH, conductivity and DO probes
STARA-ESPH	pH electrode holder for Orion Star A-series armor
STARA-ESCD	Conductivity and DO probe holder for Orion Star A-series armor
8107UWMMMD	Orion ROSS Triode 3-in-1 pH/ATC probe, gel-filled, 3m cable
087020MD	Orion RDO optical DO probe, 6m cable with stainless steel guard and calibration sleeve
087030MD	Orion RDO optical DO probe, 10m cable with stainless steel guard and calibration sleeve
087050MD	Orion RDO optical DO probe, 15m cable with stainless steel guard and calibration sleeve
087100MD	Orion RDO optical DO probe, 30m cable with stainless steel guard and calibration sleeve
1010003	Optional universal power adapter, 100-240 V, 50/60 Hz
910410	Orion pH 4.01 buffer pouches, 10/pk
910710	Orion pH 7.00 buffer pouches, 10/pk
911010	Orion pH 10.01 buffer pouches, 10/pk
911110	Orion pH rinse solution pouches, 10/pk
087010MD	Orion RDO optical DO probe, 3m cable with stainless steel guard and calibration sleeve
083005MD	Orion polarographic DO probe, 1.5m cable

- pH ■
- ISE ■
- ORP ■
- Cond ■
- RDO ■
- DO ■
- Temp ■