



Thermo Scientific Orion Star A320, A220 and A120-Series Portable Meters

Outside the laboratory, testing brings enough of its own challenges from getting the sample to taking the reading. Just because you test outside the laboratory doesn't mean your testing accuracy or quality needs to suffer. The new Orion Star A series of portable meters features a variety of advantages to handle testing in difficult environments.



Protective plugs cover RS232 and USB ports to prevent corrosion

Bright, backlit LCD display clearly shows results on those bright, sunny days as well as the dark, rainy ones and in dark areas of the plant

IP-67 waterproof housing

Ergonomic design allows for one-handed operation and features a recessed groove in the back of the meter to fit fingers easily wrapping around the meter

Keypad texture works well with gloved and wet hands

Advanced meter design prevents water ingress through all connector ports.

Do you have access to an AC power source while testing?
Save battery life by running the meter off AC power with the optional adapter





Thermo Scientific Orion Star A329 pH/ISE/Conductivity/RDO/Dissolved Oxygen Portable Meter

The Thermo Scientific Orion Star A329 pH/ISE/Conductivity/RDO/Dissolved Oxygen Portable Meter is the top choice for advanced multiparameter measurements on location. Get the information you need quickly and easily from the large, backlit graphic LCD display. Informative display can show each parameter with temperature individually or all three with temperature on one screen. Additional helpful icons include electrode status, time, date, sample ID, user ID and calibration points. Advanced features such as stability and averaging options provide additional options allowing for laboratory accuracy everywhere you need it.

Features and Benefits

- Anyone can use this meter with its plain language screen prompts, soft keys that update for easy selection and a multilanguage interface that supports English, Spanish, French, Italian, German and Chinese
- Don't miss a reading – AUTO-READ™ locks in the stable reading on your screen, ready indicator alerts when readings are stable and timed reading gathers data in specific time intervals
- Up to 5 point pH calibration with automatic recognition for USA/NIST and DIN buffers
- Fix pH and ISE calibration errors without a complete recalibration with calibration editing
- No need to worry about DO probe compatibility – the meter accepts and automatically recognizes Orion polarographic and RDO optical/luminescence-based probes
- It's easy to get accurate DO results with automatic temperature, automatic/manual barometric pressure and automatic salinity compensation when used with simultaneously with conductivity
- Calibrate for DO using water-saturated air, air-saturated water, a Winkler titration or zero point calibration
- Selectable cell constant allows for use with 2- or 4-cell conductivity cells
- For advanced accuracy in conductivity readings, selectable reading reference temperatures of 5, 10, 15, 20 or 25 °C with linear, non-linear, nLFu or USP/EP curve options
- Choice of practical salinity or natural sea water curves for salinity readings
- Linear or ISO/EN 27888 curves for TDS
- Whether you use ISE infrequently or have multiple samples every day – up to 5 point ISE calibration with advanced features such as timed end point, linear point-to-point, non-linear selectable auto-blank and low-concentration range stability
- Non-volatile memory holds up to 5000 data points with time and date stamp



- Easily transfer data and keep meter software up-to-date with the USB and RS232 ports and complimentary data analysis software
- User and sample ID fields for additional data accuracy
- Stores up to 10 methods allow for customized procedures to differentiate between tests and/or users
- Four AA batteries (included) provide over 800 hours of operation or purchase the universal power adapter (sold separately) to use AC power
- Perfectly portable, waterproof and protected to take anywhere with a IP67-rated housing
- 3 year meter replacement warranty

Product Specifications

CE TUV FCC		
pH	Range	-2.000 to 20.000
	Resolution	0.1, 0.01, 0.001
	Relative Accuracy	±0.002
	Calibration Points	Up to 5
	Calibration Editing	Yes
mV/Rel mV/ ORP	Range	±2000.0 mV
	Resolution	0.1
	Relative Accuracy	±0.2 mV or ±0.05 % of reading whichever is greater
	E _s ORP Mode	Yes
ISE	Range	0 to 19999
	Resolution	Up to 3 significant digits
	Relative Accuracy	±0.2 mV or ±0.05 % of reading whichever is greater
	Units	ppm, M, mg/L, %, ppb, none
	Calibration Points	Up to 5
	Calibration Editing	Yes
Conductivity	Calibration Features	Timed end point, linear point to point, non-linear selectable auto-blank, low concentration range stability
	Range	0.001 µS to 3000 mS
	Resolution	0.001 µS minimum; 4 significant figures minimum
	Relative Accuracy	0.5 % reading ±1 digit
	Reference Temperature	5, 10, 15, 20, 25 °C (default)
	Temperature Compensation	Linear (0 to 10.0 %/°C), nLn, nLFu, USP/EP
	Compatible Cell Constants	0.001 to 199.9
	Calibration Points	Up to 5 points
Resistivity	Calibration Editing	Yes
	Range	2 ohm to 100 meg-ohm
	Resolution	2 ohms-cm
	Relative Accuracy	0.5 % reading ±1 digit



Please turn the page...
this is just the
beginning of the
portable meters.

Product Specifications (Continued)

CE TUV FCC		
Salinity	Type	Practical salinity or natural sea water
	Range	0.01 to 80.0 psu 0.01 to 42 ppt sea water
	Resolution	0.01
	Relative Accuracy	±0.1
TDS	Range	1 to 200 ppt
	Resolution	4 significant digits
	Relative Accuracy	±0.5 % reading ±1 digit
	TDS Factor Range	Linear 0.01 to 10.00, default 0.49
Dissolved Oxygen	Concentration - Polarographic	
	Range	0 to 90 mg/L
	Resolution	0.01, 0.1
	Relative Accuracy	±0.2
	% Saturation - Polarographic	
	Range	0 to 600
	Resolution	0.1, 1
	Relative Accuracy	±2 %
	Concentration - RDO	
	Range	0 to 50 mg/L
	Resolution	0.01, 0.1
	Relative Accuracy	±0.1 mg/L up to 8 mg/L; ±0.2 mg/L from 8 to 20 mg/L; 10 % of reading from 20 to 50 mg/L
	% Saturation - RDO	
	Range	0 to 500
	Resolution	0.1, 1
	Relative Accuracy	±2 %
Automatic Barometric Pressure Correction	450.0 to 850.0 mm Hg	
Salinity Factor Correction	Automatic with separate conductivity probe or manual; 0 to 45 ppt	
Calibration Features	Water-saturated air, air saturated water, manual (Winkler) and zero point	
Probe Characteristics	Polarographic or RDO	
Temperature	Range	-5 to 105 °C, 23 to 221 °F (0 to 50 °C, 32 to 122 °F with RDO)
	Resolution	0.1
	Relative Accuracy	±0.1
	Offset Calibration	1 point
Datalogging	Number of Datalogs	5000 with time and date stamp
	Log Function	Manual, ready (includes AUTO-READ™), timed
Inputs	pH Electrode	BNC, reference pin
	Conductivity with Temperature Probe or ATC Probe	8-pin mini-DIN
	DO with Temperature Probe	9-pin mini-DIN
	Output	RS232, USB
Power	AC Adapter	Optional – universal, 100-240 VAC
	Battery Power	Included – 4 AAs
	Battery Life	800 hrs

Meter Ordering Information

Cat. No.	Description
STARA3290	Orion Star A329 pH/ISE/Conductivity/Dissolved Oxygen Portable Multiparameter Meter - Four AA batteries (installed)
STARA3295	Orion Star A329 pH/ISE/Conductivity/Dissolved Oxygen Portable Multiparameter Meter Kit - 8107UWMMMD Orion ROSS Triode 3-in-1 pH/ATC probe, 3m cable - 013010MD Orion DuraProbe conductivity cell, 3m cable - 087010MD Orion RDO optical/luminescence-based probe with 3m cable, stainless steel guard, calibration sleeve and optical/luminescence-based cap - 910410 Orion pH 4.01 buffer, 10 pouches - 910710 Orion pH 7.00 buffer, 10 pouches - 911010 Orion pH 10.01 buffer, 10 pouches - 810001 Orion ROSS electrode storage solution, 475 mL - 01100710 Orion 1413 µS conductivity standard, 10 pouches - 911110 rinse solution, 10 pouches - Protective armor with probe holders - Hard carrying case - Four AA batteries (installed)

Accessories

Cat. No.	Description
STARA-CS	Hard carrying case for Orion Star A-series portable meters
1210005	Soft carrying case for Orion Star, Star Plus and Star A-series portable meters
STARA-AR	Armor for Orion Star A-series portable meters, includes electrode holders for pH, conductivity and DO probes
STARA-ESPH	pH electrode holder for Orion Star A-series armor
STARA-ESCD	Conductivity and DO probe holder for Orion Star A-series armor
1010003	Optional universal power adapter, 100-240 V, 50/60 Hz
8107UWMMMD	Orion ROSS Triode 3-in-1 pH/ATC probe, gel-filled, 3m cable
910410	Orion pH 4.01 buffer pouches, 10/pk
910710	Orion pH 7.00 buffer pouches, 10/pk
911010	Orion pH 10.01 buffer pouches, 10/pk
911110	Orion pH rinse solution pouches, 10/pk
013010MD	Orion DuraProbe conductivity cell with 3m cable, 4-cell, K=0.475
013020MD	Orion DuraProbe conductivity cell with 6m cable, 4-cell, K=0.475
013025MD	Orion DuraProbe conductivity cell with 10m cable, 4-cell, K=0.475
011008	Orion conductivity standard, 100 µS/cm, 5 x 60 mL bottles
01100710	Orion conductivity standard pouches, 1413 µS/cm, 10/pk
01100610	Orion conductivity standard pouches, 12.9 mS/cm, 10/pk
1010001	Orion conductivity calibration resistor kit
087010MD	Orion RDO optical DO probe, 3m cable with stainless steel guard and calibration sleeve
087020MD	Orion RDO optical DO probe, 6m cable with stainless steel guard and calibration sleeve
087030MD	Orion RDO optical DO probe, 10m cable with stainless steel guard and calibration sleeve
087050MD	Orion RDO optical DO probe, 15m cable with stainless steel guard and calibration sleeve
087100MD	Orion RDO optical DO probe, 30m cable with stainless steel guard and calibration sleeve
083005MD	Orion polarographic DO probe, 1.5m cable
080513	Orion polarographic DO probe maintenance kit
080514	Orion polarographic DO probe electrolyte solution, 60 mL
080017	Calibration sleeve for Orion polarographic DO probes
087003	Replacement calibration sleeve for Orion RDO optical probes
087001	Replacement optical cap for Orion RDO probes

- pH
- ISE
- ORP
- Cond
- RDO
- DO
- Temp